

Insta-Set Roof Coating

Description

NP OneCoat is a grey or white, waterbased, polymer rubber acrylic elastomeric reflective coating for waterproofing and prolonging roof life. Special orders can be made to have product tinted any RAL colour. Minimum order quantity applies to special orders. This flexible and durable coating adheres to roofing substrates such as asphalt and metal. Protective coating withstands elongation and significantly reduces roof temperature. NP OneCoat is listed by CRRC & CA Title 24 compliant. Read and follow directions carefully. Refer to Material Safety Data Sheet for proper handling.

Preparation

Surfaces must be cleaned, dried and free of moisture on and beneath the surface. Remove dust, dirt, oil, loose granules and any other foreign contaminants. Surfaces with mildew growth should be cleaned with a bleach solution then rinsed thoroughly. Rusted metal should be cleaned with a wire brush and treated with an anti-rust treatment. Pressure washing surface is recommended for best results. It is recommended to repair all holes, leaks and cracks with NP7 Elastomagic Cement and NP F Polyester Fabric in the Three Course Installation Method. Acceptance of the substrate is the sole decision of the owner or appointed representative.

Application

For exterior use only. Protective clothing and eyewear should be used during application of this product. Apply on warm, sunny day preferably in the morning to provide maximum cure time. NP One Coat must be applied to a dry surface. Prior to application water must be swept out of all puddles, waterway and birdbaths. Temperature should be 13C and rising.

All necessary equipment needed to spray NP OneCoat will be approved and supplied by Neptune Pacific Ltd. Stir thoroughly before application to achieve a uniform consistency. Apply with professional spray equipment supplied by Neptune Pacific Ltd. Apply one coat of NP OneCoat at a rate of 11.4-22.7 litres per 9.3 square meters as indicated by system specification. Relative humidity will directly affect drying/curing time.

Cleanup

Clean tools with soap and warm water.

VOC 0.75 g/L

Chemical Ingredients

Water	CAS# 7732-18-5
Acrylic Copolymer	CAS# MIXTURE
Titanium Dioxide	CAS# 13463-67-7
Calcium Carbonate	CAS# 1317-65-3

Precautions

DO NOT STORE AT TEMPERATURES BELOW 2°C OR ABOVE 49°C. DO NOT ALLOW TO FREEZE. DO NOT APPLY WHEN HEAVY DEW OR RAIN IS EXPECTED WITHIN 24 HOURS. DO NOT THIN. Do not allow pail to tumble as this may loosen the lid and cause leakage or spillage. Drying time may vary depending upon wet film thickness, temperature, humidity and air movement.


CAUTION

KEEP OUT REACH OF CHILDREN. Close container after each use. HARMFUL OR FATAL IF SWALLOWED. EYE, SKIN, AND RESPIRATORY IRRITANT. USE WITH ADEQUATE VENTILATION. If swallowed, do not induce vomiting. Call physician immediately. In case of eye contact – flush with large amounts or room temperature water for 15 minutes, skin contact – wash thoroughly with soap and water. Irregular or stopped breathing, administer oxygen, give artificial respiration. Get immediate medical attention. Avoid prolonged breathing of vapour or spray mist. Use proper protection and adequate ventilation when using product.

For further information and advice regarding transportation, handling, storage and disposal of chemical products, users should refer to the actual Material Safety Data Sheet, which contains physical, ecological, toxicological, and other safety related data. It is highly recommended to read the actual Material Safety Data Sheet before using the product.

WARRANTY AND DISCLAIMER

Neptune Pacific Ltd warrants to the original purchaser that this product is free from any manufacturing defects that will materially affect the products performance for a period of one year. In the event there is a failure associated with the manufacturing defect of this product, Neptune Pacific shall, at its own discretion, provide the appropriate replacement product(s) or pay for the cost of the defective product only. There is no warranty for labour or installation costs of any kind. NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. NEPTUNE PACIFIC LTD SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. To the best of our knowledge, the technical data contained herein is true and accurate at the date of issuance and is subject to change without prior notice. Contact Neptune Pacific Ltd prior to ordering for the most recent and up to date data sheet. For additional limited warranty and disclaimer information contact Neptune Pacific Ltd at info@neptunepacific.co.nz

		Initial	Weathered
	Solar Reflectance	0.86	Pending
	Thermal Emittance	0.92	Pending
	Rated Product ID Number	1202-0005	
Licensed Seller ID Number	1202		
Classification	Production Line		
<small>Cool Roof Rating Council ratings are determined for a fixed set of conditions, and may not be appropriate for determining seasonal energy performance. The actual effect of solar reflectance and thermal emittance on building performance may vary.</small>			
<small>Manufacturer of product stipulates that these ratings were determined in accordance with the applicable Cool Roof Rating Council procedures.</small>			