

NP 21

Ultimate Walkway System

Description

NP 21 Ultimate Walkway System is a walkway coating formulated with aggregate to create a textured, non-slip surface to protect walking areas on smooth roofing surfaces. Creates an aesthetic, permanent, non-slip protection walk-path.

Preparation

Surfaces must be cleaned, dried, and free of moisture on and beneath the surface. Remove dust, dirt, oil, loose granules and any other foreign contaminants. Surfaces with mildew growth should be cleaned with a bleach solution then rinsed thoroughly. Rusted metal should be cleaned with a wire brush and treated with an anti-rust treatment. Pressure washing surface is recommended for best results. It is recommended to repair all holes, leaks and cracks with NP 7 Elastomagic Cement and PG F polyester fabric in the Three Course Installation Method.

Application

For exterior use only. Protective clothing and eyewear should be used during application of this product. Apply on warm, sunny day preferably in the morning to provide maximum cure time. Prior to application water must be swept out of all puddles, waterways, and birdbaths. Temperature should be 13°C and rising.

Stir thoroughly before application to achieve a uniform consistency. Apply with a heavy-duty paint roller. Apply first coat at a rate of 9.5 litres per 20 square meters. Allow a minimum of 4 hours to dry. Apply second coat at a rate of 9.5 litres per 25 square meters. Allow at least four hours between coats and 24-48 hours for full cure, dependent upon weather conditions. Relative humidity will directly affect drying/curing time.

Clean-up

Clean tools with soap and warm water.

VOC/VOS 45.74 g/l max (0.38 lbs/gal)

Chemical Ingredients

Water	CAS# 7732-18-5
Acrylic Copolymer	CAS# MIXTURE
Calcium Carbonate	CAS# 1317-65-3
Zinc Oxide	CAS# 131413-2
Yellow Oxide Paste	CAS# 51274-00-1
Propylene Glycol	CAS# 57-55-6

Precautions

DO NOT STORE AT TEMPERATURE BELOW 2° OR ABOVE 49°C. DO NOT ALLOW TO FREEZE. DO NOT APPLY WHEN HEAVY DEW OR RAIN IS EXPECTED WITHIN 24 HOURS. DO NOT THIN.

When transporting this product be sure the lid is tight and the pail is secured. Do not allow pail to tumble as this may loosen the lid and cause leakage or spillage. Drying time may vary depending upon wet film thickness, temperature, humidity and air movement.

CAUTION

KEEP OUR OF REACH OF CHILDREN. Close container after each use. HARMFUL OR FATAL IF SWALLOWED. EYE, SKIN, AND RESPIRATORY IRRITANT. USE WITH ADEQUATE VENTILATION. If swallowed, do not induce vomiting. Call physician immediately. In case of eye contact – flush with large amounts of room temperature water for 15 minutes, skin contact – wash thoroughly with soap and water. Irregular or stopped breathing, administer oxygen, give artificial respiration. Get immediate medical attention. Avoid prolonged breathing of vapour or spray mist. Use proper protection and adequate ventilation when using this product.

For further information and advice regarding transportation, handling, storage and disposal of chemical products, users should refer to the actual Material Safety Data Sheet containing physical, ecological, toxicological, and other safety related data. It is highly recommended to read the actual Material Safety Data Sheet before using the product.

WARRANTY AND DISCLAIMER

Neptune Pacific Ltd warrants to the original purchaser that this product is free from any manufacturing defects that will materially affect the products performance for a period of one year. In the event there is a failure associated with a manufacturing defect of this product, Neptune Pacific Ltd shall, at its own discretion, provide the appropriate replacement product(s) or pay for the cost of the defective product only. There is no warranty for labour or installation costs of any kind. NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. NEPTUNE PACIFIC LTD SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. To the best of our knowledge, the technical data contained herein is true and accurate at the date of issuance and is subject to change without prior notice. Contact prior to ordering for the most recent and up to date data sheet. For additional limited warranty and disclaimer information contact Neptune Pacific Ltd at info@neptunepacific.co.nz.